



Lifting Gear Hire Corporation

P: 800.878.7305 | F: 708-430-3536 | www.lgh-usa.com | sales@lgh-usa.com

600 lb Capacity Electric Cable Hoist

Beta Max - New Yorker

New Yorker



Specifications								
Model	Lifting Specifications			AC Power	Weight Unit (lbs)	Operator Control Type	Mounting Options	
	Capacity (lbs)	Height (ft)	Speed (fpm)				Scaff Trac	I-Beam Trolley
New Yorker	600	350	80	220V-20 Amp	155	Wired or Wireless Remote Control	X	X

**Double Rope. Ask about custom cable lengths. All Beta Max Hoist Systems meet or exceed ANSI & OSHA specifications.*

Mounting Options



Scaff Trac

Our most popular mounting system attaches in minutes, with no tools, to existing scaffolding and is used with all Beta Max hoists. Unlimited system lengths are available using add-on 7 ft. Scaff-Trac extensions.

Max. Load Lift* - 1200 lbs. when used with conventional scaffolding.

Outward Cantilever - 3.5 ft

Headroom - 31.00 in.



I-Beam Trolley

Our most flexible and versatile mounting system is used with all of our large capacity hoists. The addition of a rolling I-Beam Trolley Top allows many Beta Max Hoists to adapt to existing I-Beams. If the horizontal trolley is not necessary Beta Max offers a Fixed IBeam Top which firmly holds the hoist stationary on the I-Beam.

Max. Load Lift* - 2000 lbs.

Headroom - 31.25 in.