

Endcap Spreader Beams | 9 - 80 Ton | 4" & 6" End Caps | Compression Cap Load Chart

4" MaxiBar Load Chart		
Capacity in Tons 2000 lbs.		
Span (feet)	Min. Top Sling Angle 45° Sch. 160	Min. Top Sling Angle 60° Sch. 160
4-10	57	60
11	48	60
12	43	60
13	36	60
14	32	55
15	26	46
16	23	40
17	19	33
18	17	29
19	14	24
20	13	22
21	10	18
22	9	17

Green shading reflects rental inventory.

4" MaxiBar Weight Chart

4" MaxiBar End Cap: 200 lbs. Pair

4" MaxiBar Link Plate: 72 lbs. Pair

4" Schedule 160 Pipe: 22.5 lbs. per ft.

4" Pipe Deduction: 1.7 ft.

4" MaxiBar



6" MaxiBar Load Chart					
Capacity in Tons 2000 lbs.					
Span (feet)	Min. Top Sling Angle 45° Sch. 80	Min. Top Sling Angle 60° Sch. 80	Span (feet)	Min. Top Sling Angle 45° Sch. 80	Min. Top Sling Angle 60° Sch. 80
4-14	71	80	26	22	39
15	69	80	27	20	34
16	64	80	28	18	31
17	58	80	29	16	28
18	53	80	30	14	25
19	48	80	31	13	23
20	44	75	32	12	21
21	39	68	33	10	18
22	34	61	34	9	16
23	31	54	35	8	15
24	28	49	36	8	14
25	25	43	40	4	8

Green shading reflects rental inventory.

6" MaxiBar Weight Chart

6" XL End Caps: 600 lbs. Pair

6" XL Link Plates: 120 lbs. Pair

6" Schedule 80 Pipe: 28.6 lbs. per ft.

6" XL Pipe Deduction: 2 ft.

6" MaxiBar

